

Navigation and Information Commands

Listed below are direct commands the Natural Debugger provides for navigating through the debugging areas, scrolling screen displays, obtaining various information on objects and variables, and specifying profiles. For a summary of all commands available with the Natural Debugger, refer to Command Summary and Syntax.

- BREAK
 - FLIP
 - LAST
 - OBJCHAIN
 - ON/OFF
 - PROFILE
 - SCAN
 - SCREEN
 - SET OBJECT
 - STACK
 - SYSVARS
 - TEST ON/OFF
-

BREAK

The command BREAK is the default command which is automatically set when creating a new debug entry. It displays the Debug Window as described in Concepts of the Natural Debugger.

When the command BREAK is deleted upon modification of the corresponding debug entry, no Debug Window appears. However, other specified commands are executed and the event count is increased.

FLIP

The command FLIP switches between the display of the two PF-key lines (PF1 to PF12 and PF13 to PF24).

LAST

The command LAST displays the command last entered. The last three commands are stored and can be recalled.

OBJCHAIN

The command OBJCHAIN can only be used when a Natural object has been interrupted.

This command displays the objects on the current level and all superior levels, as well as the current GDA (Global Data Area), if applicable, and provides information on the interruption.

ON/OFF

When you enter the command ON/OFF in the Natural debug utility, test mode is switched on or off respectively. See also TEST ON/OFF below.

PROFILE

The command PROFILE displays the Edit Profile screen where you can modify the profile of the debugging utility.

Edit Profile Screen

The Edit Profile screen provides you with the following options:

Option	Explanation
Reset Debug Environment Automatically on Exit	Specifies an automatic reset of your current debug environment once you exit the debugging utility. The default is N (No).
File for Loading/Saving Debug Environments	Specifies to/from which system file debug environments are to be saved/loaded: FUSER (default), FNAT or SPAD (scratch-pad file).
Confirm EXIT/CANCEL Before Execution	Specifies a confirmation of an EXIT or CANCEL command before execution. The default is N (No).
Stack Unknown Commands	Specifies that any unknown debug command which is entered (for example, the name of a called program) is to be stacked. If so, once you enter an unknown debug command, you immediately exit the debugging utility and the command is executed. If this option has not been specified, an unknown debug command leads to a corresponding error message. The default is Y (Yes).
Output Device	Specifies an output device for the Call Statistics Maintenance function; the default value is HARDCOPY.
Maximum debug buffer size in KB	Specifies the maximum size (in kilobytes) of the debug buffer. The debug buffer is automatically enlarged as required, but only up to the specified maximum. Enter 0 to indicate no limit or enter a value from 4 - 16384 (must be a multiple of 4). If the limit would be exceeded, no further debug entries can be defined and no additional call or statement execution statistics entries are generated.

SCAN

Only applies to the List Object Source (see the relevant section) function.

This command searches for a string of characters within an object source:

SCAN searches for the value specified which may be delimited by blanks or by any characters that are neither letters nor numeric characters.

SCAN ABS results in an absolute scan of the source code for the specified value regardless of what other characters may surround the value.

See also the syntax diagrams in Command Summary and Syntax.

SCREEN

When you enter the command SCREEN upon interruption of a Natural object, the current screen output of the interrupted Natural object is displayed. ENTER takes you back to debug mode.

SET OBJECT

The command SET OBJECT changes the name of the default object as described in the relevant section in Start the Natural Debugger. See also the syntax of SET in the section Command Summary and Syntax.

STACK

When you enter the command STACK, the contents of the entry at the top of the Natural stack is displayed. Up to 15 individual top entry elements can be displayed. Elements longer than 55 characters are truncated and marked with an asterisk (*).

Note:

An error message is displayed if any single element is longer than 249 characters.

SYSVARS

When you enter this command, the current values of system variables are displayed.

TEST ON/OFF

The command TEST ON/OFF switches test mode on or off respectively. In the Natural debug utility, you only need to enter ON/OFF as described above.